



designed for scientists



IKA Plate (RCT digital)

/// Data Sheet

The IKA Plate (RCT digital) has a round top made of aluminum alloy. It stirs volumes of up to 20l (H₂O) and runs at speeds ranging from 50-1500rpm.

Strongly standing by its product and technology, IKA is offering a lifetime warranty on the magnetic stirrer – unparalleled in the industry; scientists can focus on their experiments with a reliable stir plate.

Some of the features are: IKA emphasizes ease-of-use by design simplicity: reduced forms and operating elements meet the modernity of smartphones: IKA not only focuses on hardened glass because of visibility, chemical resistance and safety, it also optically changes the game of a magnetic stirrer with a glass surface. The IKA Plate (RCT digital) improves over time with regular firmware updates. Using Alnico magnetic technology, the IKA Plate (RCT digital)



designed for scientists

achieves excellent temperature stability and high residual induction. It also provides for maximum vortex. The integrated timer and counter function supports the control of kinetics and sensitive reactions; the IKA SmartTemp® function protects users intelligently and predictably.

Technical Data

Number of stirring positions	1
Stirring quantity max. per stirring position (H ₂ O) [l]	20
Motor rating output [W]	9
Direction of rotation	right / left
Speed display set-value	LCD
Speed display actual-value	LCD
Speed control	Turning knob
Speed range [rpm]	50 - 1500
Setting accuracy speed [rpm]	10
Stirring bar length [mm]	30 - 80
Self-heating of the hotplate by max. stirring (RT:22°C/duration:1h) [+K]	8
Heat output [W]	600
Temperature display set-value	LCD
Temperature display actual-value	LCD
Temperature unit	°C / °F
Heating temperature range [°C]	Room temp. + device self heating - 310
Heat control	Turning knob
Temperature setting range [°C]	0 - 310
Temperature setting resolution of heating plate [K]	1
Connection for ext. temperature sensor	PT1000, ETS-D5, ETS-D6
Heating rate medium [K/min]	7
Temperature setting resolution of medium [K]	1
Adjustable safety circuit [°C]	50 - 370
Set-up plate material	Aluminium alloy
Set-up plate dimensions [mm]	Ø 135
Automatic reverse rotation	yes
Intermittend mode	yes
Viscosity trend measurement	yes
Timer	yes
Sensor in medium detection (Error 5)	yes
Speed deviation (no load, nominal voltage, at 1500rpm + 25 °C) [±%]	2
Heating rate (1l H ₂ O in H1500) [K/min]	7
Heat control accuracy of heating plate (at 100°C) [±K]	5
Heat control accuracy with ext. PT1000 (500ml H ₂ O in 600ml beaker, 40mm stirring bar, 600rpm, 50°C) [±K]	0.5
Heat control accuracy with ETS-D5 (500ml H ₂ O in 600ml beaker, 40mm stirring bar, 600rpm, 50°C) [±K]	0.5
Heat control accuracy with ETS-D6 (500ml H ₂ O in 600ml beaker, 40mm stirring bar, 600rpm, 50°C) [±K]	0.2
Dimensions (W x H x D) [mm]	160 x 85 x 270
Weight [kg]	2.4
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 42
USB interface	yes
RS 232 interface	yes
Voltage [V]	220 - 230 / 115 / 100



designed for scientists

Frequency [Hz]	50/60
Power input standby [W]	1.6
Power input [W]	650

